

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product code : Lub005018
Type of product : Lubricant

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Rymax b.v.
Delweg 8
6902 PJ Zevenaar
T +31 (0)316 740840 - F +31 (0)316 740844
info@rymax-lubricants.com - www.rymax-lubricants.com

1.4. Emergency telephone number

Emergency number : +31 (0)316 740840

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment -
Chronic Hazard Not classified

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains Reaction product of 1,3,4-thiadiazolidine-2.5-dithione, formaldehyde and phenol, heptyl derivs, Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl. May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

2.3. Other hazards

Other hazards not contributing to the classification : Flammable liquids. Prolonged or repeated skin contact with the material will remove natural oils which leads to a dermatitis. Spills of this product present a serious slipping hazard.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Gevitro GL-5 HD SAE 85W/90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]	(CAS-No.) 64742-65-0 (EC-No.) 265-169-7 (EC Index-No.) 649-474-00-6 (REACH-no) 01-2119471299-27	50 - 75	Not classified
Residual oils (petroleum), solvent-dewaxed; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of ong, branched chain hydrocarbons from a residual oil by solvent crystallization. It consists of hydrocarbons having carbon numbers predominantly greater than C25 and boiling above approximately 400 °C (752 °F).]	(CAS-No.) 64742-62-7 (EC-No.) 265-166-0 (EC Index-No.) 649-471-00-X (REACH-no) 01-2119480472-38	25 - 50	Not classified
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14-tert-alkyl	(EC-No.) 931-384-6 (REACH-no) 01-2119493620-38	0,5 - 5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Long chain alkenyl amine	(CAS-No.) 112-90-3 (EC-No.) 204-015-5 (EC Index-No.) 612-283-00-3	0,1 - 1	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410
PPD		0,5 - 1	Not classified
Reaction product of 1,3,4-thiadiazolidine-2.5-dithione, formaldehyde and phenol, heptyl derivs.	(EC-No.) 939-460-0 (REACH-no) 01-2119971727-23	0,05 - 0,5	Flam. Liq. Not classified Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Phenol, heptyl derivs. substance listed as REACH Candidate (4-heptylphenol, branched and linear [substances with a linear and/or branched alkyl chain with a carbon number of 7 covalently bound predominantly in position 4 to phenol, covering also UVCB- and well-defined substances which include any of the individual isomers or a combination thereof])	(CAS-No.) 72624-02-3 (EC-No.) 276-743-1 (REACH-no) 01-2119972228-30	< 0,05	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14-tert-alkyl	(EC-No.) 931-384-6 (REACH-no) 01-2119493620-38	(9,4 =<C < 100) Skin Sens. 1, H317 (50 =<C < 100) Eye Dam. 1, H318

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after inhalation : After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after skin contact : After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after eye contact : After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after ingestion : After adequate first aid, no further treatment is required unless symptoms reappear.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

Gevitro GL-5 HD SAE 85W/90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid spilling the product, as this might cause falls.

6.1.1. For non-emergency personnel

Protective equipment : Eliminate all ignition sources if safe to do so.

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Wear suitable protective clothing, gloves and eye/face protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

Storage temperature : 50 °C

Storage area : Store away from heat. Store in a well-ventilated place.

Special rules on packaging : Keep only in original container. Store in a closed container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14-tert-alkyl

USA - ACGIH	ACGIH TWA (mg/m ³)	5
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)		
EU	IOELV TWA (mg/m ³)	5 mg/m ³
Bulgaria	OEL TWA (mg/m ³)	5 mg/m ³
Netherlands	Grenswaarde TGG 8H (mg/m ³)	5 mg/m ³

8.2. Exposure controls

Appropriate engineering controls:

Use adequate ventilation to keep oil mist below applicable standard. Use splash goggles when eye contact due to splashing is possible. Ocular shower with suitable liquid.

Personal protective equipment:

Gloves. Safety glasses. Protective clothing. Avoid all unnecessary exposure.

Materials for protective clothing:

Wear suitable protective clothing

Hand protection:

Gevitro GL-5 HD SAE 85W/90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Neoprene or nitrile rubber gloves. Chemical resistant PVC gloves (to European standard EN 374 or equivalent). Time of penetration is to be checked with the glove producer

Eye protection:

Chemical goggles or safety glasses. Use splash goggles when eye contact due to splashing is possible. EN 166

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid prolonged and repeated contact with skin. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn

Respiratory protection:

Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Particle filter. EN 143

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Characteristics.
Colour	: light brown.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -21 °C
Boiling point	: No data available
Flash point	: 224 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 902,1 kg/m ³ @15°C
Solubility	: insoluble in water.
Log Pow	: No data available
Viscosity, kinematic	: 180 mm ² /s @40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

Minimum ignition energy	: ≈
Other properties	: See Product Data Sheet for detailed information.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

Gevitro GL-5 HD SAE 85W/90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

LD50 oral (rat)	5000 mg/kg
-----------------	------------

LD50 dermal (rat)	5000 mg/kg
-------------------	------------

LC50 inhalation (rat) (mg/l)	5,53 mg/l/4h
------------------------------	--------------

Long chain alkenyl amine (112-90-3)

LD50 oral (rat)	1689 mg/kg
-----------------	------------

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14-tert-alkyl

NOAEL (subacute, oral, animal/male, 28 days)	500 mg/kg bodyweight
--	----------------------

NOAEL (subacute, oral, animal/female, 28 days)	150 mg/kg bodyweight
--	----------------------

Aspiration hazard : Not classified

Gevitro GL-5 HD SAE 85W/90

Viscosity, kinematic	180 mm ² /s @40°C
----------------------	------------------------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Not classified.

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14-tert-alkyl

NOEC (chronic)	0,12 mg/l
----------------	-----------

Phenol, heptyl derivs. (72624-02-3)

LC50 fish 1	2,4 mg/l Rainbow Trout
-------------	------------------------

EC50 Daphnia 1	0,36 mg/l
----------------	-----------

EC50 72h algae (1)	1,2 mg/l Scenedesmus quadricauda
--------------------	----------------------------------

EC50 72h algae (2)	0,25 mg/l
--------------------	-----------

Gevitro GL-5 HD SAE 85W/90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Reaction product of 1,3,4-thiadiazolidine-2.5-dithione, formaldehyde and phenol, heptyl derivs.	
LC50 fish 1	> 1000 mg/l Pimephales promelas
EC50 Daphnia 1	41 mg/l
EC50 72h algae (1)	100 mg/l
EC50 96h algae (1)	25 mg/l
ErC50 (algae)	> 100 mg/l
NOEC (chronic)	32 mg/l
NOEC chronic fish	1000 mg/l Pimephales promelas

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l
EC50 72h algae (1)	3 mg/l

Long chain alkenyl amine (112-90-3)

LC50 fish 1	0,11 mg/l
EC50 Daphnia 1	0,011 mg/l
EC50 96h algae (1)	0,03 mg/l

12.2. Persistence and degradability

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14-tert-alkyl

Persistence and degradability	Not biodegradable.
Biodegradation	7,4 % 28 DY, OECD TG 301 B

Phenol, heptyl derivs. (72624-02-3)

Biodegradation	25,4 % 28 Days
----------------	----------------

Reaction product of 1,3,4-thiadiazolidine-2.5-dithione, formaldehyde and phenol, heptyl derivs.

Biodegradation	17,4 % 28 Days
----------------	----------------

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

Persistence and degradability	Not biodegradable.
-------------------------------	--------------------

Long chain alkenyl amine (112-90-3)

Biodegradation	66 % 28 Days
----------------	--------------

12.3. Bioaccumulative potential

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14-tert-alkyl

Log Kow	9,4
---------	-----

Phenol, heptyl derivs. (72624-02-3)

Bioconcentration factor (BCF REACH)	549,5
Log Kow	2,7 0.1 Days

Reaction product of 1,3,4-thiadiazolidine-2.5-dithione, formaldehyde and phenol, heptyl derivs.

Log Kow	9,4 0.1 Days
---------	--------------

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

Bioconcentration factor (BCF REACH)	260
Log Pow	9,2

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

Gevitro GL-5 HD SAE 85W/90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : See Directive 2001/118/EC.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : Not applicable
UN-No. (IMDG) : Not applicable
UN-No. (IATA) : Not applicable
UN-No. (ADN) : Not applicable
UN-No. (RID) : Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable
Proper Shipping Name (ADN) : Not applicable
Proper Shipping Name (RID) : Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

No data available

- Transport by sea

No data available

- Air transport

No data available

- Inland waterway transport

No data available

Gevitro GL-5 HD SAE 85W/90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

- Rail transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list $\geq 0,1$ % / SCL

Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

Reference to AwSV : Water hazard class (WGK) 3, severe hazard to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

Ministry's list of carcinogens : Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).],Residual oils (petroleum), solvent-dewaxed; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of ong, branched chain hydrocarbons from a residual oil by solvent crystalli zation. It consists of hydrocarbons having carbon numbers predominantly greater than C25 and boiling above approxi mately 400 °C (752 °F).] are listed

Ministry's list of mutagens : Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).],Residual oils (petroleum), solvent-dewaxed; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of ong, branched chain hydrocarbons from a residual oil by solvent crystalli zation. It consists of hydrocarbons having carbon numbers predominantly greater than C25 and boiling above approxi mately 400 °C (752 °F).] are listed

NON-exhaustive list of reproductive toxins - Breastfeeding : None of the components are listed

NON-exhaustive list of reproductive toxins - Fertility : None of the components are listed

NON-exhaustive list of reproductive toxins - Evolution : None of the components are listed

Denmark

Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association

Gevitro GL-5 HD SAE 85W/90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PNEC	Predicted No-Effect Concentration
PBT	Persistent Bioaccumulative Toxic
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Aquatic Chronic Not classified	Hazardous to the aquatic environment - Chronic Hazard Not classified
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. Not classified	Flammable liquids Not classified
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Reaction product of 1,3,4-thiadiazolidine-2.5-dithione, formaldehyde and phenol, heptyl derivs, Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

SDS EU (REACH Annex II) RYMAX

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness